

PINZA SALDATRICE PER ACCOPPIATO BARRIERA

THECNICAL DATE	Hpl WSZ 200	Hpl WSZ 300	Hpl WSZ 400
PTFE-uncoated	Hpl WSZ 200	Hpl WSZ 300	Hpl WSZ 400
PTFE-coated	Hpl WSZ 200 TB	Hpl WSZ 300 TB	Hpl WSZ 400 TB
Type of devices	Hand sealer		
Seal seam length	200 mm (7.9 in)	300 mm (11.8 in)	400 mm (15.7 in)
Seal seam width	12 mm (0.5 in)	12 mm (0.5 in)	12 mm (0.5 in)
Sealing temperature	50-250 °C (122-482 °F) infinitely adjustable		
Time of pre-heating	Approx. 5min.	Approx 5min.	Approx 5min.
Heating	Via stampa bove and below		
Power	350 VA	350 VA	350 VA
Mains connection	230V, 50/60 Hz 115 V 50/60 Hz	230V, 50/60 Hz 115 V 50/60 Hz	230V, 50/60 Hz 115 V 50/60 Hz
Weight	1,5 KG (2.2 lb.)	1,5 KG (2.2 lb.)	1,5 KG (2.2 lb.)

ACCESSORIES

Table clamp	WSZ-TK	WSZ-TK	WSZ-TK
-------------	--------	--------	--------